Drying cabinets, ironing board cabinets, utility sinks and dehumidifiers. All manufactured in Sweden.





Contents >

- 03 Introduction
- 04 Drying cabinets
- 14 Ironing board cabinets
- 16 Utility sinks
- 26 Nimo Pro



Introduction >



New clothes – every wash.



Cabinet control

All of our Eco drying cabinets use either heat pump technology or extract air technology with sensor control. This means that you don't have to think about either power levels or time. When the laundry is dry, the drying cabinet turns off – completely automatically. To find these drying cabinets, look for the Eco Dryer label!

Nimo's products are all manufactured in Sweden. For more than 50 years we have manufactured the products that help you look after your clothes so they last longer.

In this brochure we present these products so that you can easily choose from the market's widest range of energy-efficient drying cabinets, ironing board cabinets and utility sinks for both home and professional environments.

www.nimoverken.com

Drying Cabinets >



There are many ways of drying wet clothes. But only one is energy efficient and gentle. A drying cabinet from Nimo dries your clothes in the best possible way.

A drying cabinet dries everything from wet shoes and dirty children's snowsuits to your most delicate garments. Nimo's drying cabinets with ECO Dryer technology have built-in humidity sensors which shut off the unit when the clothes are dry.

Our drying cabinet with heat pump technology, the ECO Dryer 2.0 HP, goes even further and offers the market's most energy-efficient way of drying wet laundry. It has even won awards for "Lowest price per dry" and "Most electrical energy-efficient drying equipment".





The prize-winning and heat pump powered Eco Dryer 2.0 HP drying cabinet is the market's most energy efficient way of drying clothes. The NB 1000 TMS utility sink (page 21) is a handy utility sink with both baskets and enclosed sections.



Every garment in the drying cabinet

There are garments which cannot be tumble dried; they shrink, become crumpled or quite simply ruined. The symbol on the care label says that it can't be tumble dried, but you won't find a "do not use drying cabinet" symbol. Because you can dry everything in a drying cabinet: exercise clothes, snowsuits, shirts, blouses and

skirts – everything!
If you want to take extra care of your clothes, a drying cabinet is the safest drying choice.
A sensor-controlled drying cabinet also makes your clothes smoother and pleasantly warm when you take them out of the cabinet (you can never over-dry your garments).



Hello! I'm Nimo, the raccoon!
You can dry garments overnight
in a drying cabinet, with the door
ajar and the heat turned off. On
www.nimoverken.se/torkskolan
you can find more of my top tips.

We have drying cabinets of different types and in different price classes. The difference lies primarily in how energy-efficient they are and where they should be installed.

Choose between heat pump technology or extract air technology which is sensor or timer-controlled.







Heat pump hero

Our most energy-efficient drying cabinet is based upon heat pump technology and requires no extract air connection. Overall, the ECO Dryer 2.0 HP is the market's most effective, quietest and most energy-efficient drying cabinet, using 65% less energy than a traditional drying cabinet. So it's good for the environment, simple to install and easy on your wallet!

The intelligent cabinet with sensor control

The great thing about this drying cabinet is the sensor control, which means it turns off automatically when the laundry is dry. It has three pull-out, folding hangers and the warm moist air is led away through the ventilation duct on top of the cabinet. Our intelligent drying cabinet is our most popular because the sensor control system gives a significantly lower energy consumption than traditional drying cabinets.

Traditional drying cabinet with timer

A real classic! Here you decide both time and temperature. And when you use it right, a drying cabinet with a timer is a prudent budget choice; for example, a half full cabinet of garments is dry in only 1–2 hours on half power. The ETS 1900 is an easy-to-position timer cabinet with pull-out, folding hangers. The warm moist air is led out through the ventilation duct on the top of the cabinet.









Bas

Perfect for the family!

Extreme


Perfect for preschools or ski cabins!

Bod

Perfect for the workplace!

Accessories

Article RSK No. F. No Article No. 1. Door hanger 67000947 9200032 8035887 9205902 2. Glove rack 67001164 8035683 3. Shoe rack 1700/1900 60090001 8035682 9205903





Drying Cabinets www.nimoverken.com



Eco Dryer 2.0 HP Drying Cabinet

Floor standing, 1,930 mm

The award-winning Eco Dryer 2.0 HP is by far the market's most effective, quietest and most energy-efficient drying cabinet. You save up to 65% energy compared with a traditional drying cabinet with timer. The drying cabinet uses heat pump technology and can be installed without an extract air duct. The drying cabinet is available in white in the fitting levels Bas, Extreme or Bod. Glove racks in the doors and shoe racks are included in all models.



Dim. (H x W x D) Weight Protection class Capacity Noise level Electrical connection

95 kg

Performance **Energy consumption**

Drying system

IP24, SEMKO and CE approved Hanging length 16 metres, normal load 4 kg Normal wall outlet, one phase 230 V 10 \hbox{A} 22 g water per minute 1.3 kWh with normal load (4 kg*),

1930 × 595 × 675 mm

down to 0.28 kW/kg with maximum load. Heat pump technology – requires no extract air ventilation. Condensation water container and integrated condensation hose included (Bod: condensation hose only).

White


Fitting/Door hanging		Article No.	RSK No.	E No.
A Bas	Left	65110100	8035860	9200002
	Right	65120100	8035865	9200003
B Extreme	Left	65110101	8035861	9200004
	Right	65120101	8035866	9200005
C Bod	Left	65110102	8035862	9200006
	Right	65120102	8035868	9200007


Titanium


Fitting/Door hanging			Article No.	RSK No.	E No.
A	Bas	Left Right	65110200 65120200		

Diagle

ыаск				
Fitting/Do	or hanging	Article No.	RSK No.	E No.
A Bas	Left Right	65110300 65120300		9200010 920001









Drying Cabinets



ETS 1900 E Drying Cabinet Floor standing, 1,915 mm

Floor standing model with three pull-out and foldable hangers. The warm moist air is led out through the ventilation duct on the top of the cabinet. The inside of the door is fitted with door hangers. Supplied with right or left hung door, which can even be altered retrospectively. The drying cabinet is equipped with sensorcontrolled automatic shut-off and has two fixed programmes together with manual timer control. The sensor system means that the drying cabinet only uses as much energy as it needs.



Dim. (H x W x D) Weight

1915 × 595 × 615 mm 61 kg

Protection class Capacity

Fan capacity

Drying system

IP24, SEMKO and CE approved Hanging length 16 metres, volume 4.5 kg and up Below 60 db(A)

Noise level Electr. connection One phase 230 V 10 A, heater power 1500 W,

motor 35 W with overheat protection 180 m³ of which 25% is evacuated Extract air. Supplied with ventilation

connections

White

Fitting/Door ha	anging	Article No.	RSK No.	E No.
D Bas	Left	62110101	8035838	9295144
	Right	62120101	8035839	9295145
E Extreme	Left	62110122	8035853	9295165
	Right	62120122	8035854	9295164
F Bod	Left	62110127	8035855	9200025
	Right	62120127	8035856	9200026

Titanium


Fitting/Door hanging			Article No.	RSK No.	E No.
D	Bas	Left	62110200	8035842	9295146
		Right	62120200	8035843	9295147


Plack

DIC	ick				
Fitting/Door hanging		Article No.	RSK No.	E No.	
D	Bas	Left	62110300	8035844	9295148
		Right	62120300	8035845	9295149

Bas: 3 hangers + 3 door hangers

10





Drying Cabinets

Sensor-controlled Eco Extract Air

ETS 1700 E Drying Cabinet

Floor standing, 1,715 mm

Floor standing model with three pull-out and foldable hangers. The warm moist air is led out through the ventilation duct on the top of the cabinet. The inside of the door is fitted with door hangers. Supplied with right or left hung door, which can even be altered retrospectively. The drying cabinet is equipped with sensorcontrolled automatic shut-off and has two fixed programmes together with manual timer control. The sensor system means that the drying cabinet only uses as much energy as it needs.



Dim. (H x W x D) 1715 × 595 × 615 mm Weight

56 kg

Protection class IP24, SEMKO and CE approved Hanging length 16 metres, Capacity

volume 4 kg and up Below 60 db(A)

Noise level Electr. connection One phase 230 V 10 A, heater power 1500 W,

> motor 35 W with overheat protection 180 m³ of which 25% is evacuated Extract air. Supplied with ventilation

Drying system connections

White

Fan capacity

Fitt	ing/Doo	r hanging	Article No.	RSK No.	E No.
D	Bas	Left	61110101	8035832	9295152
		Right	61120101	8035833	9295153

Titanium

Fitting/Door hanging		Article No.	RSK No.	E No.		
	D	Bas	Left	61110201	8035834	9295154
			Right	61120201	8035835	9295155

ETS 1500 E Drying Cabinet

Wall-mounted, 1,435 mm

Wall-mounted model with pull-down hanger system for comfortable working height. The warm moist air is led out through the ventilation duct on the top or side of the cabinet. The drying cabinet fits perfectly in positions such as above the washing machine. The drying cabinet is equipped with sensorcontrolled automatic shut-off and has two fixed programmes together with manual timer control. The sensor system means that the drying cabinet only uses as much energy as it needs.



Dim. (H x W x D) 1435×595×610 mm

Weight 60 kg

Protection class IP24, SEMKO and CE approved Hanging length 16 metres, Capacity volume 4 kg and up

Noise level Below 60 db(A)

Electr. connection One phase 230 V 10 A, heater power 1500 W,

motor 35 W with overheat protection 180 m³ of which 25% is evacuated Fan capacity Drying system Extract air. Supplied with ventilation

connections

White

Door hanging	Article No.	RSK No.	E No.
Left	63110101	8035848	9295158
Right	63120101	8035849	9295159

Titanium

Door hanging	Article No.	RSK No.	E No.
Left	63110200	8035850	9295160
Right	63120200	8035851	9295161

Drying Cabinets 11 www.nimoverken.com

Drying Cabinets Extract Air Timer



ETS 1900 Drying Cabinet Floor standing, 1,915 mm

Floor standing model with three pullout, folding hangers. The hot moist air is led away through the ventilation duct on the top of the cabinet. The inside of the door is also fitted with three door hangers. Supplied with right or left hung door, which can even be altered retrospectively. Timer-controlled fan, stepless heating.



Dim. (H x W x D) Protection class Capacity


Noise level Electr. connection

Fan capacity Drying system

1915 × 595 × 615 mm IP24, SEMKO and CE approved Hanging length 16 metres, volume 4 kg and up Below 60 db(A) One phase 230 V 10 A, heater power $1500\,\mbox{W},$ motor $35\,\mbox{W}$ with overheat protection 180 m³ of which 25% is evacuated Extract air. Supplied with ventilation connections

White

Fitting/Door hanging		Article No.	RSK No.	E No.	
G	Bas	Left Right	62110100 62120100	8035836 8035837	9295140 9295141
Н	Bod	Left Right		8035840 8035841	9295142 9295143





Bod: 10 ceiling clothing hooks + 3 door hangers

Drying Cabinets

Extract Air Timer

ETS 1700 Drying Cabinet Floor standing, 1,715 mm

Floor standing model with three pull-out, folding hangers. The hot moist air is led away through the ventilation duct on the top of the cabinet. The inside of the door is also fitted with three door hangers. Supplied with right or left hung door, which can even be altered retrospectively. Timer-controlled fan, stepless heating.



Dim. (H x W x D) Weight Protection class

Capacity

Noise level Electr. connection

Fan capacity Drying system 1715 × 595 × 615 mm 56 kg

IP24, SEMKO and CE approved Hanging length 16 metres, volume 4 kg and up Below 60 db(A)

One phase 230 V 10 A, heater power 1500 W, motor 35 W with overheat protection 180 m³ of which 25% is evacuated Extract air. Supplied with ventilation

connections

White

Fitting/Door hanging G Bas

Article No. RSK No.

61110100 8035830 9295150 61120100 8035831 9295151

ETS 1500 Drying Cabinet Wall-mounted, 1,435 mm

Wall-mounted model with pull-down hanger system for comfortable working height. The warm moist air is led out through the ventilation duct on the top or side of the cabinet. The drying cabinet fits perfectly in positions such as above the washing machine. Timer-controlled fan, stepless heating.



Dim. (H x W x D) Weight **Protection class**

Capacity Noise level

Fan capacity Drying system

Electr. connection

1435×595×610 mm 60 ka

IP24, SEMKO and CE approved Hanging length 16 metres,

volume 4 kg and up Below 60 db(A)

One phase 230 V 10 A, heater power 1500 W, motor 35 W with overheat protection

180 m³ of which 25% is evacuated Extract air. Supplied with ventilation

connections

White

Door hanging Article No. RSK No. E No. 63110100 8035846 9295156 Right 63120100 8035847 9295157

ETS 1100 Drying Cabinet

Wall-mounted, 1,140 mm

Compact drying cabinet for wallmounting, for example in bathrooms. Timer-controlled fan, fixed heating. Reversible door.



Dim. (H x W x D) Weight

Protection class Capacity

Noise level Electr. connection

Fan capacity Drying system 1140×595×335 mm 33 kg

IP24, SEMKO and CE approved Hanging length 5.4 metres, volume approx. 1.5 kg and up Below 60 db(A)

One phase 230 V 10 A, heater power

1500 W, motor 35 W with overheat protection 150 m³ of which 25% is evacuated Extract air. Supplied with ventilation

connections

White

Door hanging	Article No.	RSK No.	E No.
Reversible	60003011	8035852	929513

12 **Drying Cabinets** 13 www.nimoverken.com



Convenient but concealed.

Can a usable product be attractive?
Of course it can! The solution:
a wall-mounted ironing board
cabinet.

The ironing board is usually hidden away when not in use, perhaps because it is not very attractive. But it is extremely practical and is used often. With a wall-mounted ironing board cabinet, you can easily unfold, iron and then conceal your ironing board. The cabinet has a timer and space for both the ironing board and accessories. It doesn't get better or more attractive than this!

On the one hand, or on the other

The ironing boards in our ironing board cabinets can be raised, lowered and turned so that you can easily iron from any side. You can also choose whether the door on the ironing board cabinet is right or left hung. This means that you can position the ironing board cabinet where it suits you best.



► IronMaid®

Wall-mounted, 1,313 mm

The ironing board can be rotated and height adjusted. The cabinet has space for your iron, which is connected to the built-in electrical outlet with timer function. IronMaid® is available in three different colours.

Dim. (H x W x D) $1313 \times 372 \times 280$ mm

Article No. 50050007	RSK No. 8035702	E No. 9295131
Titanium		
Article No.	RSK No.	E No.
50050009	8035703	9295132
Black		
Article No.	RSK No.	E No.
50050008	8035684	9295133

Utility sinks



Your utility sink is the A–Z. This is where you sort the laundry, and where you fold it. So choose your utility sink carefully.

Do you have the space and the need for a large, small or in-between unit? Completely enclosed, partially enclosed or open? In white, black or titanium? We have utility sinks in many sizes, shapes and price classes. You choose! But regardless of which one you choose, your utility sink will always have the following:

- Height-adjustable legs
- A sink with a rounded base
- Stainless steel surfaces with non-drip edging

All enclosed utility sinks also have:

- Fully integrated plinths
- Doors with door dampers





In this laundry room, the NB 1000L utility sink (page 18) is combined with the ETS 1900 E drying cabinet, which has sensorcontrolled shut-off (page 10).



Tough materials

In a laundry room, it's often warm and rather humid. For this reason, all of Nimo's utility sinks are manufactured in tough materials: they neither swell nor warp and are completely free from wood and fibre-based materials. They're simply there, year after year, ready for use. We call that quality.



Utility sinks >

NB 1200 L Utility Sink

Completely enclosed, 1,200 mm

Utility sink with double work surface and central sink. The unit contains six large wire baskets and lockable detergent storage. Double storage pocket in door, door dampers, concealed hinges and fully integrated plinth.



Dim. (H x W x D) 900 × 1200 × 600 mm Sink (L x W x D) 400 × 400 × 220 mm

White

Sink position	Article No.	RSK No.
Centre	52000019	8034224

Titanium

Sink position	Article No.	RSK No.	
Centre	52001019	8034266	

Black

Sink position	Article No.	RSK No.
Centre	52002019	8034267



NB 1000 L Utility Sink

Completely enclosed, 1,000 mm

Utility sink with large work surface and sink. The unit contains three large wire baskets and lockable detergent storage. Double storage pocket in door, door dampers, concealed hinges and fully integrated plinth.



Dim. (H x W x D) 900×1000×600 mm Sink (L x W x D) 400×400×220 mm

White

Sink position	Article No.	RSK No.
Left	52000009	8034210
Right	52000010	8034211

Titanium

Sink position	Article No.	RSK No.
Left	52001009	8034260
Right	52001010	8034261

Black

Sink position	Article No.	RSK No.
Left	52002009	8034264
Right	52002010	8034265









NB 800 L Utility Sink

Completely enclosed, 800 mm

Utility sink with work surface and sink. The unit contains three narrow wire baskets and lockable detergent storage. Double storage pocket in door, door dampers, concealed hinges and fully integrated plinth.

Dim. (H x W x D) $900 \times 800 \times 600$ mm Sink (L x W x D) 400×400×220 mm

Sink position	Article No.	RSK No.
Left	52000005	8034206
Right	52000006	8034207

Utility sinks

Our utility sinks are completely free from wood and fibrebased sheet material which can warp or crack in humid environments.





NB 500 L Utility Sink

Completely enclosed, 500 mm

Compact unit with sink. The unit contains lockable detergent storage. Double storage pocket in door, door dampers, concealed hinges and fully integrated plinth.

Dim. (H x W x D) 900 × 500 × 600 mm Sink (L x W x D) 400 × 400 × 220 mm

White

Article No. 52000001	RSK No. 8034200
Article No. 52001003	RSK No. 8034262
Article No. 52002001	RSK No. 8034263
	52000001 Article No. 52001003 Article No.





NB 1200 TMSk Utility Sink

Completely enclosed, 1,200 mm

Spacious unit with sink. Lockable detergent storage under sink with double storage pocket in door, built-in door dampers, concealed hinges and fully integrated plinth. Intelligent storage with three large wire baskets behind the second door. Available in white.

Dim. (H x W x D) 900×1200×600 mm Sink (L x W x D) 370×340×160 mm

White

Sink position	Article No.	RSK No.
Left	52000064	8034254
Right	52000065	8034255



NB 1200 TMS Utility Sink

Partially enclosed, 1,200 mm

Utility sink with sink and space for washing machine. The unit contains lockable detergent storage. Double storage pocket in door, door dampers, concealed hinges and fully integrated plinth.

Dim. (H x W x D) 900×1200×600 mm Sink (L x W x D) 400×400×220 mm

White

Sink position	Article No.	RSK No.
Left	52000021	8034228
Right	52000022	8034229



N

NB 1000 TMS Utility Sink

Partially enclosed, 1,000 mm

Half-enclosed utility sink with large work surface and sink. The unit contains three large wire baskets and lockable detergent storage. Double storage pocket in door, door dampers, concealed hinges and fully integrated plinth.

Dim. (H x W x D) 900×1000×600 mm Sink (L x W x D) 400×400×220 mm

White

Sink position	Article No.	RSK No.
Left	52000013	8034218
Right	52000014	8034219



NB 800 TMS Utility Sink

Partially enclosed, 800 mm

Half-enclosed utility sink with work surface and sink. The unit contains three narrow wire baskets and lockable detergent storage. Double storage pocket in door, door dampers, concealed hinges and fully integrated plinth.

Dim. (H x W x D) 900 × 800 × 600 mm Sink (L x W x D) 400 × 400 × 220 mm

White

Sink position	Article No.	RSK No.
Left	52000003	8034204
Right	52000004	8034205



20 Utility sinks www.nimoverken.com

Open

NB 1200 MB Utility Sink

Unassembled, 1,200 mm

Utility sink with space for washing machine. Large work surface and sink together with fully integrated plinth. Reversible for left/right positioning. Lockable door with door dampers and concealed hinges available as option. The unit is supplied unassembled.



Dim. (H x W x D) 900×1200×600 mm Sink (L x W x D) 370×340×160 mm

White

Sink position	Article No.	RSK No.	
Reversible	52000025	8034249	
Titanium			
Sink position	Article No.	RSK No.	
Reversible	52001025	8034258	
Black			
Sink position	Article No.	RSK No.	
Reversible	52002025	8034259	



NB 1000 MB Utility Sink

Unassembled, 1,000 mm

Utility sink with open storage and three large wire baskets. Large work surface and sink together with fully integrated plinth. Reversible for left/right positioning. Lockable door with door dampers and concealed hinges available as option. The unit is supplied unassembled.



Dim. (H x W x D)	900×1000×600 mm
Sink (L x W x D)	370 × 340 × 160 mm

White

Sink position	Article No.	RSK No.
Reversible	52000017	8034248
Titanium		
Sink position	Article No.	RSK No.
Reversible	52001017	8034256
Black		
Sink position	Article No.	RSK No.
Reversible	52002017	8034257



Utility sinks >

Open

Door kit MB

Lockable door with door dampers and concealed hinges. Supplementary for our utility sinks.



Colour/Door hanging	Article No.	RSK No.
White/Left	52000031	8034250
White/Right	52000032	8034251
Titanium/Left	52001031	8034252
Titanium/Right	52001032	8034253
Black/Left	52002031	8034268
Black/Right	52007032	8034269

NB 1800 MB Utility Sink

Unassembled, 1,800 mm

Utility sink with space for washing machine and tumble drier Large work surface and sink together with fully integrated plinth. The unit has lockable doors with double storage pockets, concealed hinges and door dampers. The unit is supplied unassembled.

Dim. (H x W x D) 900×1800×600 mm Sink (L x W x D) 370×340×160 mm

White

Sink position	Article No.	RSK No.
Left	52000057	8034247
Right	52000058	8034246

NB 1200 Utility Sink

Open, 1,200 mm

Open utility sink with double worksurface and central sink. The unit has six wire baskets and a zinc electroplated chassis.

Dim. (H x W x D) 900 × 1200 × 600 mm Sink (L x W x D) 400 × 400 × 220 mm

White

Sink position	Article No.	RSK No.
Centre	50000022	8034031



NB 1000 Utility Sink


Open, 1,000 mm

Open unit with sink. The unit has three wire baskets and zinc electroplated chassis. The unit is reversible for left/right positioning.

Dim. (H x W x D) 900×1000×600 mm Sink (L x W x D) 400×400×220 mm

Sink position	Article No.	RSK No.
Reversible	50000021	8034030





Nimo Pro presents the products that save money in small and medium laundry rooms...

... for example in tenant-owner associations, apartment blocks, schools, construction workplaces, riding arenas and ice rinks. Here many people wash and dry their clothes with the same equipment – often 24 hours a day. So we know that you're looking for the highest quality products with long lifetimes and really low energy consumption. When you buy a drying cabinet from Nimo with heat pump technology, you can quickly earn back that investment. The Nimo Pro range includes drying cabinets, ironing boards, utility sinks, sinks, cold ironers, drying room dehumidifiers and other accessories that belong in a large laundry room.





All of our **Nimo Pro** drying cabinets either use heat pump technology or extract air technology with sensor control. They are so energy-efficient that you quickly earn back your investment in the property's laundry room.

Nimo Eco Dryer is a guarantee for both energy-efficient drying and money-saving.



Hello, it's Nimo here. Drying cabinets with heat pump technology are closed systems and require no extract air connection. So as well as incredibly energy-efficient and silent drying, the drying cabinet can be positioned exactly where you want. On www.nimoverken.se/torkskolan you can find more of my top tips.







FT 120 VP Drying Cabinet

Floor standing, 2,060 mm

The FT 120 VP Drying Cabinet is our most energyefficient and effective drying cabinet, combining heat pump technology that gives exceptionally low running costs with high capacity and simple installation. The built-in lighting gives good illumination of the 20 foldout hangers in stainless steel. The heat pump and all of the electronics are at the top, which facilitates servicing.

Dim. (H x W x D) 2059 × 1195 × 658 mm Weight 189 kg

Protection class IP24, SEMKO and CE approved Hanging length 18 metres, normal load Capacity

6 kg, drying time 60 minutes

Noise level 55 db(A)

400V 3N AC 50Hz Electrical connection

Quick drying 50 g water per minute (6 kg 50% residual humidity)

0.35 kWh per kilo dry weight Power consumption Heat pump technology -Drying system requires no extract air ventilation

White

Article No.	RSK No.	E No.
61920011	8035871	9200014
61920001	8035872	9200015
61920012	8035882	9200017
61920002	8035884	9200018
	61920011 61920001 61920012	61920011 8035871 61920001 8035872 61920012 8035882

FT 120 FL Drying Cabinet

Floor standing, 1,860 mm

The sensor-controlled FT 120 FL is a quick-drying and energy-efficient drying cabinet with extract air technology. The cabinet works using underpressure, which eliminates leakage of air into the surrounding room. The built-in lighting gives good illumination of the 20 foldout hangers in stainless steel. The fluff filter and all of the electronics are in the top section of the cabinet, which facilitates servicing.

Dim. (H x W x D) 1860×1200×650 mm

Weight 145 kg Protection class

IP24, SEMKO and CE approved

Capacity

Hanging length 18 metres, normal load 6 kg

laundry, drying time 55 minutes Noise level

Electrical connecti 400V 3N AC 50Hz

70~g water per minute (6 kg 53% residual humidity) Quick drying

0.7 kWh per kilo dry weight Drying system Extract air technology

	Article No.	RSK No.	E No.
Reversible	61910001	8035873	9200013
Disabled user*			
Reversible	61910002	8035885	9200016

^{*} Suitable for disabled users. Touch panel for disabled use positioned in the centre of the right hand door for easy access.







FT 60 VP/Eco Dryer 2.0 HP

Floor standing, 1,930 mm

The FT 60 VP/ECO Dryer 2.0 HP drying cabinet is by far the market's most effective, quiet and energy-efficient drying cabinet, which dries laundry completely without radiators. The heat pump technology means that the drying cabinet does not require any extract air connection, which makes it much easier to install. Supplied with three hangers, two glove racks and a shoe rack.

1930×595×675 mm Dim. (H x W x D) Weight

95 kg

Protection class

IP24, SEMKO and CE approved Hanging length 16 metres, normal load 4 kg Capacity

Noise level **Electrical connection**

52 db(A) Normal wall outlet, one phase 230 V 10 A

Performance 22 g water per minute on 1.3 kWh with normal load (4 kg*),

Energy consumpti

down to 0.28 kW/kg with maximum load Heat pump technology – requires no extract

air ventilation. Condensation water container and integrated condensation hose included.

White

Drying system

Door hanging	Article No.	RSK No.	E No.
Left	65110104	8035876	920002
Right	65120104	8035877	920002

Accessories

Article	Article No.	RSK No.	E No.
1. Door hanger	67000947	8035887	9200032
2. Shoe rack HP	67001471	8035889	9200033
3. Shoe rack HP	65100001	8035890	9200034
Dad			



=

KM 80 Cold Ironer

The **KM 80 Cold Ironer** has a practical control bar that controls the 80 cm-wide aluminium rollers. The items are collected in a practical collector below the fold-down work table and the cold ironer has an automatic shut-off.

White

Dim. (H x W x D)	Article No.	RSK No.	E No.
1060×970×860 mm	55001110	8035874	9200012



IronMaid® Ironing Board

A wall-mounted, fully adjustable ironing board. It can be raised, lowered and rotated for the best possible working position.

White

Dim. (H x W)	Article No.	RSK No.	E No.
300 × 1300 mm	50050010	8035888	9200030

31 www.nimoverken.com





NB 1000 Professional & NB 1200 Professional

Open unit

Height-adjustable legs, sink with rounded base, sturdy stainless steel worktops with non-drip edging. Waste pipe for floor drain. Corrosion protected powder coating with white chassis and black legs. The NB 1000 Professional and NB 1200 Professional are reversible.

Dim. of unit (H x W x D) 900 × 1000 × 600 mm Dim. of sink 900×1200×600 mm (H x W x D) 400 × 400 × 220

White

Model	Article No.	RSK No.	E No.
NB 1000 Profession	onal 52000068	8034270	9200020
NB 1200 Profession	nal 52000072	8034271	9200019



Contra Professional Dehumidifier

Model 1200 & 2000

Our Contra laundry room dehumidifier dries clothes and keeps the air fresh and free of moisture. Suitable for drying rooms of 10-30 m². The dehumidifier is connected to the overflow outlet and extracts the collected water with an energy consumption of a mere 15–20% of other methods on the market.

	Contra 1200	Contra 2000
Dim. (H x W x D)	700×580×410	700×580×410
Air quantity m3/h	1500	1500
Electr. connection Vol	lt 220	380/220 3 phase
Output kW	1.3	1.7
Fuse	10 Ampere slow-blow	10 Ampere slow-blow
Time relay	included	included
Safety switch	included	included
Hygrostat	accessory	accessory
Electrical battery	-	accessory
35 kW		





White

Model	Article No.	RSR No.	E No.
Contra 1200	61200018	8035879	9200022
Contra 2000	61200010	8035878	9200021
Accessories			
* ** *	Australia Ata	DOLLAR	
Article	Article No.	RSK No.	E No.
1. Washing line 5 m	61200015	8035881	9200024



TL 40, TL 50 & TL 60 Sink

22. 34 & 47 litre

Hand wash sink in stainless steel for wallmounting. Supplied with wall brackets and R 32 drain outlet.

TL 40

Dim. (L x W x D) 480 × 380 × 190 mm	Capacity 22 L	Article No. 10002500	RSK No. 8032161
TL 50			
Dim. (L x W x D) 555×455×230 mm	Capacity 34 L	Article No. 10002200	RSK No. 8032138
TL 60			
Dim. (L x W x D) 660×510×250 mm	Capacity 47 L	Article No. 10002100	RSK No. 8032112



TL 50 INB & TL 60 INB Sink

34 & 47 litre

Hand wash sink in stainless steel for builtin installation. Supplied with brackets and tensioner, R 32 drain outlet with plug and chain and overflow outlet.

TL 50 INB

Dim. (L x W x D)	Capacity	Article No.	RSK No.
555 × 455 × 230 mm	34 L	10002800	8032120
TL 60 INB			
Dim. (L x W x D)	Capacity	Article No.	RSK No.
650 × 510 × 250 mm	47 L	10002050	8032121




TL 60 B Sink

47 litre

Hand wash sink in stainless steel with zinc electroplated legs. Supplied with wall bracket and R 32 drain outlet.

TL 60 B

Dim. (L x W x D)	Capacity	Article No.	RSK No.
660×510×250,	47 L	10002000	8032104
900 mm inc. legs			



SL 50, SL 60 & SL 70 Rinse Sink

40, 80 & 105 litre

Rinse sink in stainless steel for wallmounting. Supplied with epoxy-coated brackets, R 32 drain outlet with plug and chain and overflow outlet.



SL 50

Dim. (L x W x D)	Capacity	Article No.	RSK No.
560×460×200 mm	40 L	11005000	8031510

SL 60

Dim. (L x W x D)	Capacity	Article No.	RSK No.
660×510×300 mm	80 L	11006000	8031536

SL 70

Dim. (L x W x D)	Capacity	Article No.	RSK No.
760×560×300 mm	105 L	11007000	8031544



105 & 220 litre

Sink in stainless steel. Supplied with scrubbing board in stainless steel and R 32 drain outlet.





105 litre

Dim. (L x W x D)	Article No.	RSK No
775×560×300,	11007100	803411
900 mm inc. legs		

Zinc electroplated wall brackets and adjustable legs.

220 litre

Dim. (L x W x D)	Articl
850 x 650 x 475 mm,	71122
900 mm including legs	

Zinc electroplated legs with adjustable feet.

im. (L x W x D)	Article No.	RSK No.
50 x 650 x 475 mm,	71122600	8034112
00 mm including legs		

Lint Drawer

24, 42 & 80 litre

Lint drawer for washing machine.



24 Lint Drawer

Dim. (L x W x D)	Article No.	RSK No.	E No.
610×250×185 mm	80918035	8034113	9209328

42 Lint Drawer

Dim. (L x W x D)	Article No.	RSK No.	E No.
820×340×197 mm	80918037	8034114	9209330

80 Lint Drawer

Dim. (L x W x D)	Article No.	RSK No.	E No.
820 × 420 × 250 mm	80918002	8034115	9200027

Plinth

200 mm & 295 mm

Galvanised powder coated plinth for maximum durability.



Low plinth

Dim. (L x W x D)	Article No.	RSK No.	E No.
596×496×200 mm	80918047	8034116	9200035

High plinth

Dim. (L x W x D)	Article No.	RSK No.	E No.
596 × 496 × 295 mm	80918048	8034117	9200036



34 Nimo Pro

