

KTS 2000 IDEAL

Drying cabinets with mounted shoe drying system



sample picture: KTS 2000 including Blow 10 shoe dryer installed on the left side (viewed from the front)



programmable
24 hour timer



plug ready



6 hour
clock timer

KTS 2000 ideal

height (in mm)	1950
width incl. Blow 10 (in mm)	1150
depth (in mm)	780
weight (in kg)	170
power consumption (watts)	1400

Design like the KTS 2000, but with mounted shoe drying panels for up to 20 pairs of shoes and boots. The installation side (left and/or right) is optional. The shoe dryer can be switched separately from the drying cabinet.

Installation examples:

For 10 pairs of shoes and boots:
Blow 10 on left or right side

For 20 pairs of shoes and boots:
Two Blow 10, one on the left side and one on the right side

Advantages

- simple and efficient drying process
- rotary disc includes 18 hooks for clothes
- 6 hour clock timer
- programmable 24 hour timer
- on/off switch
- shoe dryer can be switched separately

Optional accessories & upgrades

- metal grate on the floor of the cabinet (surcharge)
- exhaust pipe
- LED timer, quartz controlled, current program remains active even when the unit is currentless
- LED temperature setting
- possible temperature up to 80° Celsius
- glove adaptors for shoe dryer

Technical details

- electr. connection: 230 volts~/50Hz (Euro plug)
- made of sheet steel, powder-coated
standard color: light-grey
- maintenance free radial fan
- maintenance free stepping gear motor
- cylinder lock